NSN 5985-01-179-5468

Fixed Attenuator - Page 1 of 2

Fsc Application Data: Microwave equipment



view Online at https://aerobasegroup.com/nsn/5965-01-179-5466
Application Design:
Transmission line
Body Material:
Metal
Body Style:
1b round, terminal/terminals in opposite surface
Body Surface Treatment:
Any acceptable
Overall Length:
2.300 inches
Overall Diameter:
0.550 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.30 and 1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Bnc
Power Rating:
2.0 watts average and 2.0 kilowatts peak
Rf Signal Attenuation In Decibels:
20.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+2.0 gigahertz
Connection Type Per Function:
Female output and male input
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 2.000 gigahertz
Test Data Document:
81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-a-3933/19 government specification

NSN 5985-01-179-5468

Fixed Attenuator - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000