NSN 5985-01-180-4099

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-180-4099

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

2.880 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches

Overall Height:

1.900 inches

Overall Width:

2.560 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.260 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.750 inches

End Application:

An/alq-122/b52

Voltage Standing Wave Ratio:

1.30

Coaxial Connector Series Designation:

Bnc and sma

Power Rating:

2.0 watts average

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.2

Overall Attenuation Range In Decibels:

+0.0/+10.0

Attenuation Variation Method:

Stepped

Step Position Quantity:

10

Attenuation Per Step In Decibels:

1.0

Mounting Facility Type And Quantity:

4 threaded hole

Frequency Range:

Between 0.000 hertz and 1.000 gigahertz

NSN 5985-01-180-4099

Variable Attenuator - Page 2 of 2



Overall Attenuation Accuracy In Decibels: -0.20/+0.20 Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft **Mounting Facility Pattern:** Four position diamond Shaft Type: Round, slotted Mounting Facility Screw Thread Diameter: 0.138 inches Impedance Rating In Ohms: 50.0 input-output **Terminal Type And Quantity:** 2 connector, coaxial, female Shelf Life: N/a Unit Of Measure: ---Demilitarization: Yes - demil/mli Fiig: A223a0