NSN 5985-01-181-4834

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-181-4834

Application Design:

Transmission line

Body Style:

Irregular

Overall Length:

2.620 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.740 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.240 inches

Overall Height:

0.500 inches

Overall Width:

1.810 inches

Unthreaded Mounting Hole Diameter:

0.125 inches

Voltage Standing Wave Ratio:

1.60

Coaxial Connector Series Designation:

Sma

Power Rating:

1.0 watts average

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.8

Overall Attenuation Range In Decibels:

+0.0/+40.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole

Frequency Range:

Between 0.500 gigahertz and 1.000 gigahertz

Adjustment Device Type And Quantity:

1 electronic, voltage controlled

Mounting Facility Pattern:

Four position rectangular

Terminal Type And Quantity:

3 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

NSN 5985-01-181-4834

Variable Attenuator - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A223a0

