

View Online at <https://aerobasegroup.com/nsn/5985-01-183-6523>

**Application Design:**

Transmission line

**Body Style:**

Irregular

**Voltage Standing Wave Ratio:**

1.30 and 1.40 and 1.50

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

1.0 watts average

**Insertion Loss At Minimum Attenuation In Maximum Decibels:**

0.5

**Overall Attenuation Range In Decibels:**

+0.0/+80.0

**Attenuation Variation Method:**

Stepped

**Step Position Quantity:**

80

**Attenuation Per Step In Decibels:**

1.0

**Mounting Facility Type And Quantity:**

1 free standing base

**Frequency Range:**

Between 0.000 hertz and 1.500 gigahertz

**Overall Attenuation Accuracy In Decibels:**

-1.00/+1.00

**Adjustment Device Type And Quantity:**

2 knob w/dial

**Impedance Rating In Ohms:**

50.0 input-output

**Terminal Type And Quantity:**

2 connector, coaxial, female

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A223a0