## NSN 5985-01-183-8036

Fixed Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-183-8036

Application Design:
Transmission line
Body Style:
1b round, terminal/terminals in opposite surface
Overall Length:
1.170 inches
Overall Diameter:
0.350 inches
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Osm
Rf Signal Attenuation In Decibels:
5.0
Attenuation Accuracy In Decibels:
,
-0.50/+0.50
•
-0.50/+0.50
-0.50/+0.50  Terminal Type And Quantity:
-0.50/+0.50  Terminal Type And Quantity: 2 connector
-0.50/+0.50  Terminal Type And Quantity: 2 connector  Frequency Range:
-0.50/+0.50  Terminal Type And Quantity: 2 connector  Frequency Range: Between 0.000 gigahertz and 5.000 gigahertz
-0.50/+0.50  Terminal Type And Quantity: 2 connector  Frequency Range: Between 0.000 gigahertz and 5.000 gigahertz  Shelf Life:
-0.50/+0.50  Terminal Type And Quantity: 2 connector  Frequency Range: Between 0.000 gigahertz and 5.000 gigahertz  Shelf Life: N/a
-0.50/+0.50  Terminal Type And Quantity: 2 connector  Frequency Range: Between 0.000 gigahertz and 5.000 gigahertz  Shelf Life: N/a
-0.50/+0.50  Terminal Type And Quantity: 2 connector  Frequency Range: Between 0.000 gigahertz and 5.000 gigahertz  Shelf Life: N/a  Unit Of Measure:
-0.50/+0.50  Terminal Type And Quantity: 2 connector  Frequency Range: Between 0.000 gigahertz and 5.000 gigahertz  Shelf Life: N/a  Unit Of Measure:  Demilitarization:
-0.50/+0.50  Terminal Type And Quantity: 2 connector  Frequency Range: Between 0.000 gigahertz and 5.000 gigahertz  Shelf Life: N/a  Unit Of Measure:  Demilitarization: Yes - demil/mli
-0.50/+0.50  Terminal Type And Quantity: 2 connector  Frequency Range: Between 0.000 gigahertz and 5.000 gigahertz  Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: