

View Online at <https://aerobasegroup.com/nsn/5985-01-185-0652>

Cross Sectional Shape:

Internal, rectangular double ridged external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.720 inches second flange

Flange Inside Height:

0.321 inches second flange

Flange Outside Width:

1.375 inches second flange

Flange Outside Height:

1.375 inches second flange

Flange Depth:

0.250 inches second flange

Flange Connecting Hole Diameter:

0.144 inches second flange all connection facilities and 0.147 inches second flange all connection facilities

Insertion Loss In Decibels:

0.15

Thread Qty Per Inch (tpi):

32 first flange all connection facilities

Maximum Operating Pressure:

45.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.960 inches and 1.250 inches

Thread Size:

0.138 inches first flange all connection facilities

Waveguide Inside Width:

0.720 inches

Waveguide Inside Height:

0.321 inches

Waveguide Outside Height:

Between 0.510 inches and 0.690 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Contact, double ridge type second flange

Waveguide Length:

21.000 inches

Flexibility:

Flexible single tubing segment

Material:

Aluminum alloy all tubing segment and flange

Surface Treatment:

Chromate all tubing segment and flange outside surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc first flange all connection facilities

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0