

View Online at <https://aerobasegroup.com/nsn/5985-01-185-0652>

**Cross Sectional Shape:**

Internal, rectangular double ridged external, rectangular

**Thread Class:**

2b first flange all connection facilities

**Thread Direction:**

Right-hand first flange all connection facilities

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.720 inches second flange

**Flange Inside Height:**

0.321 inches second flange

**Flange Outside Width:**

1.375 inches second flange

**Flange Outside Height:**

1.375 inches second flange

**Flange Depth:**

0.250 inches second flange

**Flange Connecting Hole Diameter:**

0.144 inches second flange all connection facilities and 0.147 inches second flange all connection facilities

**Insertion Loss In Decibels:**

0.15

**Thready Qty Per Inch (tpi):**

32 first flange all connection facilities

**Maximum Operating Pressure:**

45.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 0.960 inches and 1.250 inches

**Thread Size:**

0.138 inches first flange all connection facilities

**Waveguide Inside Width:**

0.720 inches

**Waveguide Inside Height:**

0.321 inches

**Waveguide Outside Height:**

Between 0.510 inches and 0.690 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole second flange all connection facilities

**Flange Style:**

Contact, double ridge type second flange

**Waveguide Length:**

21.000 inches

**Flexibility:**

Flexible single tubing segment

**Material:**

Aluminum alloy all tubing segment and flange

**Surface Treatment:**

Chromate all tubing segment and flange outside surfaces

**Style Designator:**

Straight type

**Thread Series Designator:**

Unc first flange all connection facilities

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0