NSN 5985-01-185-0701

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-185-0701

| Application Design: |
|--|
| Transmission line |
| Body Material: |
| Steel |
| Body Style: |
| Err-090 |
| Overall Length: |
| 1.150 inches |
| Overall Diameter: |
| 0.375 inches |
| Operating Tempurature Range: |
| -20.0/+65.0 degrees celsius |
| End Application: |
| An/spg-55b |
| Voltage Standing Wave Ratio: |
| 1.25 and 1.30 |
| Input Impedance Rating In Ohms: |
| 50.0 |
| Output Impedance Rating In Ohms: |
| 50.0 |
| Coaxial Connector Series Designation: |
| Sma |
| Power Rating: |
| 1.0 watts average and 1.0 kilowatts peak |
| Rf Signal Attenuation In Decibels: |
| 10.0 |
| Voltage Standing Wave Ratio Frequency Range: |
| +0.0/+5.0 gigahertz and +5.0/+7.0 gigahertz |
| Attenuation Accuracy In Decibels: |
| -0.50/+0.50 |
| Connection Type Per Function: |
| Female input and male output |
| Mounting Method: |
| Connector |
| Terminal Type And Quantity: |
| 2 connector |
| Frequency Range: |
| Between 0.000 hertz and 7.000 gigahertz |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 5985-01-185-0701

Fixed Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A20000