NSN 5985-01-185-1510

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-185-1510

Cross	Sectional	Shane.
C1055	Sectional	Snape.

Internal, rectangular external, rectangular

End Application:

An/dpm-2 (v) 4

Tubing Wall Construction Style:

Seamless single tubing segment

Tubing Twist Type:

Straight twist single tubing segment

Tubing Twist Angle In Deg:

90.0 single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.005 inches all flanges

Flange Inside Height:

0.505 inches all flanges

Flange Outside Width:

1.625 inches all flanges

Flange Outside Height:

1.625 inches all flanges

Flange Depth:

0.438 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.05

Waveguide Outside Width:

1.000 inches

Waveguide Inside Width:

0.900 inches

Waveguide Inside Height:

0.400 inches

Waveguide Outside Height:

0.500 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges all connection facilities

Flange Style:

Cover type all flanges

Waveguide Length:

6.000 inches

Flexibility:

Flexible single tubing segment

NSN 5985-01-185-1510

Waveguide Assembly - Page 2 of 2

Fiig: A073a0



Material:
Copper alloy all tubing segment and flange
Precious Material And Location:
Internal surfaces silver and internal surfaces rhodium
Precious Material:
Silver and rhodium
Surface Treatment:
Silver all tubing segment and flange inside surfaces and rhodium all tubing segment and flange inside surfaces
Style Designator:
Straight type
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No