NSN 5985-01-185-1529

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-185-1529

Application Design:
Transmission line
Body Style:
Irregular
Overall Length:
4.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length
3.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.000 inches
Overall Height:
0.400 inches
Overall Width:
2.250 inches
Unthreaded Mounting Hole Diameter:
0.150 inches
Voltage Standing Wave Ratio:
1.70
Coaxial Connector Series Designation:
Sma
Power Rating:
500.0 milliwatts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
2.3
Overall Attenuation Range In Decibels:
+0.0/+40.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 9.000 gigahertz and 11.000 gigahertz
Adjustment Device Type And Quantity:
1 electronic, current controlled
Mounting Facility Pattern:
Four position rectangular
Terminal Type And Quantity:
1 connector, coaxial, female and 1 connector, coaxial, male and 2 turret
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5985-01-185-1529

Variable Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A223a0