NSN 5985-01-185-1529

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-185-1529

Application Design:

Transmission line

Body Style:

Irregular

Overall Length:

4.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches

Overall Height:

0.400 inches

Overall Width:

2.250 inches

Unthreaded Mounting Hole Diameter:

0.150 inches

Voltage Standing Wave Ratio:

1.70

Coaxial Connector Series Designation:

Sma

Power Rating:

500.0 milliwatts average

Insertion Loss At Minimum Attenuation In Maximum Decibels:

2.3

Overall Attenuation Range In Decibels:

+0.0/+40.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole

Frequency Range:

Between 9.000 gigahertz and 11.000 gigahertz

Adjustment Device Type And Quantity:

1 electronic, current controlled

Mounting Facility Pattern:

Four position rectangular

Terminal Type And Quantity:

1 connector, coaxial, female and 1 connector, coaxial, male and 2 turret

Shelf Life:

N/a

Unit Of Measure:

NSN 5985-01-185-1529

Variable Attenuator - Page 2 of 2

Demilitarization:

No

Fiig:

A223a0

