NSN 5985-01-185-1530

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-185-1530

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.522 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.500 inches
Overall Height:
4.500 inches
Overall Width:
4.500 inches
Unthreaded Mounting Hole Diameter:
0.154 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
3.500 inches
End Application:
5840-01-141-4378
Voltage Standing Wave Ratio:
1.55
Coaxial Connector Series Designation:
Sma
Sma Power Rating:
Power Rating:
Power Rating: 5.0 watts average and 500.0 watts peak
Power Rating: 5.0 watts average and 500.0 watts peak Overall Attenuation Range In Decibels:
Power Rating: 5.0 watts average and 500.0 watts peak Overall Attenuation Range In Decibels: +6.0/+66.0
Power Rating: 5.0 watts average and 500.0 watts peak Overall Attenuation Range In Decibels: +6.0/+66.0 Attenuation Variation Method:
Power Rating: 5.0 watts average and 500.0 watts peak Overall Attenuation Range In Decibels: +6.0/+66.0 Attenuation Variation Method: Stepped
Power Rating: 5.0 watts average and 500.0 watts peak Overall Attenuation Range In Decibels: +6.0/+66.0 Attenuation Variation Method: Stepped Step Position Quantity:
Power Rating: 5.0 watts average and 500.0 watts peak Overall Attenuation Range In Decibels: +6.0/+66.0 Attenuation Variation Method: Stepped Step Position Quantity: 60
Power Rating: 5.0 watts average and 500.0 watts peak Overall Attenuation Range In Decibels: +6.0/+66.0 Attenuation Variation Method: Stepped Step Position Quantity: 60 Attenuation Per Step In Decibels:
Power Rating: 5.0 watts average and 500.0 watts peak Overall Attenuation Range In Decibels: +6.0/+66.0 Attenuation Variation Method: Stepped Step Position Quantity: 60 Attenuation Per Step In Decibels: 1.0
Power Rating: 5.0 watts average and 500.0 watts peak Overall Attenuation Range In Decibels: +6.0/+66.0 Attenuation Variation Method: Stepped Step Position Quantity: 60 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity:
Power Rating: 5.0 watts average and 500.0 watts peak Overall Attenuation Range In Decibels: +6.0/+66.0 Attenuation Variation Method: Stepped Step Position Quantity: 60 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 unthreaded hole
Power Rating: 5.0 watts average and 500.0 watts peak Overall Attenuation Range In Decibels: +6.0/+66.0 Attenuation Variation Method: Stepped Step Position Quantity: 60 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 unthreaded hole Frequency Range:
Power Rating: 5.0 watts average and 500.0 watts peak Overall Attenuation Range In Decibels: +6.0/+66.0 Attenuation Variation Method: Stepped Step Position Quantity: 60 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 unthreaded hole Frequency Range: Between 0.000 hertz and 1.500 gigahertz
Power Rating: 5.0 watts average and 500.0 watts peak Overall Attenuation Range In Decibels: +6.0/+66.0 Attenuation Variation Method: Stepped Step Position Quantity: 60 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 unthreaded hole Frequency Range: Between 0.000 hertz and 1.500 gigahertz Adjustment Device Type And Quantity:
Power Rating: 5.0 watts average and 500.0 watts peak Overall Attenuation Range In Decibels: +6.0/+66.0 Attenuation Variation Method: Stepped Step Position Quantity: 60 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 unthreaded hole Frequency Range: Between 0.000 hertz and 1.500 gigahertz Adjustment Device Type And Quantity: 1 knob w/dial

50.0 input-output

NSN 5985-01-185-1530

Variable Attenuator - Page 2 of 2



Terminal Type Ar	nd Quantity:
------------------	--------------

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0