

View Online at <https://aerobasegroup.com/nsn/5985-01-187-4959>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Bend Angle In Deg:

90.0 all bends h-plane

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

0.620 inches all flanges and 0.624 inches all flanges

Flange Inside Height:

0.309 inches all flanges and 0.313 inches all flanges

Flange Outside Width:

1.297 inches all flanges and 1.327 inches all flanges

Flange Outside Height:

1.297 inches all flanges and 1.327 inches all flanges

Flange Inside Diameter:

0.985 inches first flange and 1.015 inches first flange

Flange Depth:

0.360 inches all flanges and 0.390 inches all flanges

Flange Connecting Hole Diameter:

0.144 inches second flange all connection facilities and 0.147 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.10

Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

Thread Size:

0.138 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.620 inches and 0.625 inches

Waveguide Inside Height:

Between 0.309 inches and 0.314 inches

Waveguide Outside Height:

Between 0.388 inches and 0.394 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Center To Center Distance:

3.800 inches

Waveguide Height:

1.150 inches

Special Features:

Flange face one end 63.0 in. Microinch finish

Flexibility:

Rigid all tubing segment

Material:

Copper alloy all tubing segment and flange

Style Designator:

Double bend type

Thread Series Designator:

Unc first flange all connection facilities

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0