

View Online at <https://aerobasegroup.com/nsn/5985-01-187-6858>

**Cross Sectional Shape:**

Internal, rectangular double ridged external, rectangular

**Thread Class:**

2b first flange all connection facilities

**Thread Direction:**

Right-hand first flange all connection facilities

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.720 inches second flange

**Flange Inside Height:**

0.321 inches second flange

**Flange Outside Width:**

1.375 inches second flange

**Flange Outside Height:**

1.375 inches second flange

**Flange Depth:**

0.250 inches second flange

**Flange Connecting Hole Diameter:**

0.144 inches second flange all connection facilities and 0.147 inches second flange all connection facilities

**Voltage Standing Wave Ratio:**

1.30

**Insertion Loss In Decibels:**

0.60

**Thready Qty Per Inch (tpi):**

32 first flange all connection facilities

**Maximum Operating Pressure:**

45.0 pounds per square inch gage

**Waveguide Outside Width:**

0.730 inches

**Thread Size:**

0.138 inches first flange all connection facilities

**Waveguide Inside Width:**

0.720 inches

**Waveguide Inside Height:**

0.321 inches

**Waveguide Outside Height:**

0.421 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole second flange all connection facilities

**Waveguide First Leg Length:**

1.040 inches

**Flange Style:**

Contact, double ridge type second flange

**Waveguide Second Leg Length:**

20.880 inches

**Waveguide Third Leg Length:**

5.480 inches

**Waveguide Fourth Leg Length:**

2.100 inches

**Flexibility:**

Rigid single tubing segment

**Material:**

Aluminum alloy all tubing segment and flange

**Surface Treatment:**

Chromate all tubing segment and flange outside surfaces

**Style Designator:**

Three bend type

**Thread Series Designator:**

Unc first flange all connection facilities

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0