## NSN 5985-01-187-8093

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:

**Body Surface Treatment:** 

Metal

Err-090

**Body Style:** 

Any acceptable

Overall Length:



View Online at https://aerobasegroup.com/nsn/5985-01-187-8093

| 2.660 inches   |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|
| Overall Diameter:  |  |  |  |  |  |  |  |
| 0.830 inches   |  |  |  |  |  |  |  |
| Voltage Standing Wave Ratio:   |  |  |  |  |  |  |  |
| 1.15 and 1.25  |  |  |  |  |  |  |  |
| Input Impedance Rating In Ohms:  |  |  |  |  |  |  |  |
| 50.0   |  |  |  |  |  |  |  |
| Output Impedance Rating In Ohms:   |  |  |  |  |  |  |  |
| 50.0   |  |  |  |  |  |  |  |
| Coaxial Connector Series Designation:  |  |  |  |  |  |  |  |
| N  |  |  |  |  |  |  |  |
| Power Rating:  |  |  |  |  |  |  |  |
| 2.0 watts average and 300.0 watts peak   |  |  |  |  |  |  |  |
| Rf Signal Attenuation In Decibels:   |  |  |  |  |  |  |  |
| 40.0   |  |  |  |  |  |  |  |
| Voltage Standing Wave Ratio Frequency Range:   |  |  |  |  |  |  |  |
| +0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz   |  |  |  |  |  |  |  |
| Attenuation Accuracy Reference Frequency:  |  |  |  |  |  |  |  |
| 12.4 gigahertz   |  |  |  |  |  |  |  |
| Attenuation Accuracy In Decibels:  |  |  |  |  |  |  |  |
| -0.75/+0.75  |  |  |  |  |  |  |  |
| Connection Type Per Function:  |  |  |  |  |  |  |  |
| Female input and male output   |  |  |  |  |  |  |  |
| Mounting Method:   |  |  |  |  |  |  |  |
| oungoun.ou.  |  |  |  |  |  |  |  |
| Connector  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |
| Connector  |  |  |  |  |  |  |  |
| Connector Terminal Type And Quantity:  |  |  |  |  |  |  |  |
| Connector  Terminal Type And Quantity: 2 connector   |  |  |  |  |  |  |  |
| Connector Terminal Type And Quantity: 2 connector Frequency Range:   |  |  |  |  |  |  |  |
| Connector  Terminal Type And Quantity: 2 connector  Frequency Range: Between 0.000 hertz and 12.400 gigahertz  |  |  |  |  |  |  |  |
| Connector  Terminal Type And Quantity: 2 connector  Frequency Range: Between 0.000 hertz and 12.400 gigahertz  Fsc Application Data:   |  |  |  |  |  |  |  |
| Connector  Terminal Type And Quantity: 2 connector  Frequency Range: Between 0.000 hertz and 12.400 gigahertz  Fsc Application Data: Antennas, waveguides, and related equipment |  |  |  |  |  |  |  |

## NSN 5985-01-187-8093

Fixed Attenuator - Page 2 of 2



|  |  | eas |  |
|--|--|-----|--|

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000