NSN 5985-01-187-8093

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:

Body Surface Treatment:

Metal

Err-090

Body Style:

Any acceptable

Overall Length:



View Online at https://aerobasegroup.com/nsn/5985-01-187-8093

2.660 inches							
Overall Diameter:							
0.830 inches							
Voltage Standing Wave Ratio:							
1.15 and 1.25							
Input Impedance Rating In Ohms:							
50.0							
Output Impedance Rating In Ohms:							
50.0							
Coaxial Connector Series Designation:							
N							
Power Rating:							
2.0 watts average and 300.0 watts peak							
Rf Signal Attenuation In Decibels:							
40.0							
Voltage Standing Wave Ratio Frequency Range:							
+0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz							
Attenuation Accuracy Reference Frequency:							
12.4 gigahertz							
Attenuation Accuracy In Decibels:							
-0.75/+0.75							
Connection Type Per Function:							
Female input and male output							
Mounting Method:							
oungoun.ou.							
Connector							
Connector							
Connector Terminal Type And Quantity:							
Connector Terminal Type And Quantity: 2 connector							
Connector Terminal Type And Quantity: 2 connector Frequency Range:							
Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz							
Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Fsc Application Data:							
Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Fsc Application Data: Antennas, waveguides, and related equipment							

NSN 5985-01-187-8093

Fixed Attenuator - Page 2 of 2



		eas	

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000