NSN 5985-01-190-1336

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-190-1336

Application Design:
Transmission line
Body Material:
Steel, corrosion resisting
Body Style:
Err-090
Body Surface Treatment:
Passivated, qq-p-35
Overall Length:
2.750 inches
Overall Diameter:
0.812 inches
Operating Tempurature Range:
+13.0/+33.0 degrees celsius
Voltage Standing Wave Ratio:
1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Rf Signal Attenuation In Decibels:
10.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.75/+0.75
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Special Features:
7 mm type sexless coupling required on input
Precious Material And Location:
Contact surfaces gold
·
Precious Material:
Gold
Gold

NSN 5985-01-190-1336

Fixed Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A20000