NSN 5985-01-190-6838

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-190-6838

Application Design:
Transmission line
Body Material:
Brass
Body Style:
Err-090
Body Surface Treatment:
Nickel plated
Overall Length:
1.700 inches
Overall Diameter:
0.430 inches
End Application:
6625-01-144-4481
Voltage Standing Wave Ratio:
1.30 and 1.60
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Rf Signal Attenuation In Decibels:
30.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+0.5 gigahertz and +0.5/+1.0 gigahertz
Attenuation Accuracy Reference Frequency:
1.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Connection Type Per Function:
Female input and male output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 1.000 gigahertz
Fsc Application Data:
Antennas, waveguides and related equip.
Shelf Life:
N/a

NSN 5985-01-190-6838

Fixed Attenuator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000