

View Online at <https://aerobasegroup.com/nsn/5985-01-191-4142>

Body Style:

Rectangular

Overall Length:

2.750 inches

Overall Height:

0.900 inches

Overall Width:

2.310 inches

Frequency Rating:

0.0 gigahertz single frequency voltage standing wave ratio and 3.0 gigahertz single frequency voltage standing wave ratio

Unthreaded Mounting Hole Diameter:

0.140 inches

Switch Type:

Nontransfer

Operating Temperature Range:

-35.0/+85.0 degrees celsius

End Application:

5840-01-147-7235

Voltage Standing Wave Ratio:

1.20 single

Insertion Loss In Decibels:

0.20 single

Coaxial Connector Series Designation:

N

Connector End Design:

Female

Minimum Crosstalk Rating In Decibels:

80.0 single

Actuator Operating Method:

Solid state

Actuator Current Type And Rating In Amps:

0.24 dc

Actuator Voltage In Volts:

28.0

Switch Operation Sequence:

Makes before breaks

Switching Time:

20.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

2 unthreaded hole

Mounting Facility Pattern:

Two position in-line single mounting facility pattern

Material:

Copper alloy contact (s)

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Surface Treatment:

Nickel body outside surfaces

Terminal Type And Quantity:

3 solder stud and 3 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0