NSN 5985-01-191-9107



Tixed / illeridator Tage Tot 2
View Online at https://aerobasegroup.com/nsn/5985-01-191-9107
Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Passivated
Overall Length:
2.660 inches
Overall Diameter:
0.827 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.20 and 1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
5.0 watts average and 1.0 kilowatts peak
Rf Signal Attenuation In Decibels:
4.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+6.0 gigahertz and +6.0/+12.4 gigahertz
Attenuation Accuracy Reference Frequency:
12.4 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Unpackaged Unit Weight:
2.600 ounces
Mounting Method:

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 12.400 gigahertz

Precious Material And Location:

Female contact surfaces gold

NSN 5985-01-191-9107

Fixed Attenuator - Page 2 of 2



Precious Material:	
Gold	
Fsc Application Data:	
Antennas, waveguides, and related equipment	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

Fiig: A20000