

View Online at <https://aerobasegroup.com/nsn/5985-01-192-7794>

**Application Design:**

Printed circuit board

**Body Style:**

Irregular

**Overall Length:**

2.000 inches

**Overall Height:**

0.400 inches

**Overall Width:**

1.000 inches

**End Application:**

Simulator, countermeasures signals, an/ulq-13

**Voltage Standing Wave Ratio:**

1.35

**Insertion Loss At Minimum Attenuation In Maximum Decibels:**

6.0

**Overall Attenuation Range In Decibels:**

+0.5/+63.5

**Attenuation Variation Method:**

Stepped

**Step Position Quantity:**

7

**Attenuation Per Step In Decibels:**

0.5 and 1.0 and 2.0 and 4.0 and 8.0 and 16.0 and 32.0

**Frequency Range:**

Between 30.000 megahertz and 500.000 megahertz

**Overall Attenuation Accuracy In Decibels:**

-0.15/+0.15

**Adjustment Device Type And Quantity:**

1 electronic, voltage controlled

**Impedance Rating In Ohms:**

50.0 input-output

**Terminal Type And Quantity:**

38 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A223a0