NSN 5985-01-195-7375

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-195-7375

viev	V Online at https://aerobasegroup.com/nsn/5985-01-195-7375
• •	lication Design:
Trar	nsmission line
Bod	ly Style:
Coa	xial type
Ove	rall Length:
5.10	0 inches
Ove	rall Height:
1.70	0 inches
Ove	rall Width:
2.90	0 inches
Volt	age Standing Wave Ratio:
1.35	and 1.70
Coa	xial Connector Series Designation:
Sma	a
Pow	ver Rating:
1.0	watts average and 100.0 watts peak
Inse	rtion Loss At Minimum Attenuation In Maximum Decibels:
0.40	
Ove	rall Attenuation Range In Decibels:
+0.0	/+70.0
Atte	nuation Variation Method:
Step	pped
Step	o Position Quantity:
7	
Atte	nuation Per Step In Decibels:
10.0	
Μοι	inting Facility Type And Quantity:
2 co	nnector
Free	quency Range:
Betv	veen 0.000 hertz and 18.000 gigahertz
Ove	rall Attenuation Accuracy In Decibels:
-0.1	0/+0.10
Adjı	ustment Device Type And Quantity:
1 kn	ob
Terr	ninal Type And Quantity:
2 co	nnector, coaxial, female
She	If Life:
N/a	
Unit	Of Measure:
Den	nilitarization:

Yes - demil/mli

NSN 5985-01-195-7375

Variable Attenuator - Page 2 of 2

Fiig: A223a0

