NSN 5985-01-199-0009

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-199-0009

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
8.192 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
6.070 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.100 inches
Overall Height:
1.240 inches
Overall Width:
2.050 inches
End Application:
An/trc-177
Voltage Standing Wave Ratio:
1.35 and 1.50 and 1.70
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average and 500.0 watts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+70.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
7
Attenuation Per Step In Decibels:
10.0
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Mounting Thread Quantity:
32 per inch

Adjustment Device Type And Quantity:

1 electronic, voltage controlled

NSN 5985-01-199-0009

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern: Four position rectangular Mounting Facility Screw Thread Diameter: 0.138 inches Impedance Rating In Ohms: 50.0 input-output Terminal Type And Quantity: 2 connector, coaxial, female and 6 pin Shelf Life: N/a Unit Of Measure: -Demilitarization:

No Fiig: A223a0