# NSN 5985-01-200-2787

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-200-2787

# **Cross Sectional Shape:**

Internal, rectangular external, rectangular

# **Thread Class:**

2b first flange all connection facilities

# **Thread Direction:**

Right-hand first flange all connection facilities

# **Tubing Wall Construction Style:**

Seamless single tubing segment

# Flange Quantity:

2

### Flange Inside Width:

0.747 inches first flange and 0.753 inches first flange

### Flange Inside Height:

0.372 inches second flange and 0.378 inches second flange

### Flange Outside Width:

1.485 inches second flange and 1.515 inches second flange

# Flange Outside Height:

1.485 inches second flange and 1.515 inches second flange

### Flange Inside Diameter:

1.126 inches first flange and 1.156 inches first flange

# Flange Depth:

0.485 inches second flange and 0.515 inches second flange

# Flange Connecting Hole Diameter:

0.144 inches second flange all connection facilities and 0.147 inches second flange all connection facilities

# Voltage Standing Wave Ratio:

1.10

**Insertion Loss In Decibels:** 

0.35

Maximum Operating Pressure:

10.0 pounds per square inch gage

# Waveguide Outside Width:

Between 0.847 inches and 0.853 inches

# Thread Size:

0.138 inches first flange all connection facilities

#### Waveguide Inside Width:

Between 0.747 inches and 0.753 inches

# Waveguide Inside Height:

Between 0.372 inches and 0.378 inches

# Waveguide Outside Height:

Between 0.472 inches and 0.478 inches

# Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

# NSN 5985-01-200-2787

Waveguide Assembly - Page 2 of 2



Flange Style: Cover type second flange Waveguide Length: 24.000 inches Flexibility: Flexible single tubing segment Material: Copper alloy all tubing segment and flange **Precious Material And Location:** Internal surfaces silver **Precious Material:** Silver Surface Treatment: Silver all tubing segment and flange inside surfaces **Style Designator:** Straight type **Thread Series Designator:** Unc first flange all connection facilities **Fsc Application Data:** Antennas, waveguides, and related equipment Shelf Life: N/a Unit Of Measure: Demilitarization:

Yes - demil/mli

Fiig:

---

A073a0