

View Online at <https://aerobasegroup.com/nsn/5985-01-200-2789>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.747 inches first flange and 0.753 inches first flange

Flange Inside Height:

0.372 inches first flange and 0.378 inches first flange

Flange Outside Width:

1.485 inches second flange and 1.515 inches second flange

Flange Outside Height:

1.485 inches second flange and 1.515 inches second flange

Flange Depth:

1.141 inches second flange and 1.171 inches second flange

Flange Connecting Hole Diameter:

0.144 inches second flange all connection facilities and 0.147 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.10

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.847 inches and 0.853 inches

Thread Size:

0.138 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.747 inches and 0.753 inches

Waveguide Inside Height:

Between 0.372 inches and 0.378 inches

Waveguide Outside Height:

Between 0.472 inches and 0.478 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Length:

Between 3.950 inches and 4.050 inches

Flexibility:

Flexible single tubing segment

Material:

Copper alloy all tubing segment and flange

Precious Material And Location:

Internal surfaces silver

Precious Material:

Silver

Surface Treatment:

Silver all tubing segment and flange inside surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc first flange all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0