NSN 5985-01-200-2790

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-200-2790

Cross	Sa	ction	nal	Sha	no.
CIOSS	Se	CUOI	าลเ	Sna	ıbe:

Internal, rectangular external, rectangular

Bend Angle In Deg:

75.0 single bend e-plane

End Application:

Radar set an/spg-51d

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Depth:

0.360 inches all flanges

Voltage Standing Wave Ratio:

1.05

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.995 inches and 2.005 inches

Waveguide Inside Width:

Between 1.867 inches and 1.877 inches

Waveguide Inside Height:

Between 0.867 inches and 0.877 inches

Waveguide Outside Height:

Between 0.995 inches and 1.005 inches

Waveguide Longer Offset Distance:

15.210 inches

Flange Style:

Contact type all flanges

Waveguide Offset Distance:

8.640 inches

Flexibility:

Rigid single tubing segment

Material:

Metal all tubing segment and flange

Surface Treatment:

Paint all tubing segment and flange outside surfaces

Style Designator:

Bend type

Fsc Application Data:

Antennas, waveguides and related equip.

Shelf Life:

N/a

NSN 5985-01-200-2790

Waveguide Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0