Radio Frequency Transmission Line Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-200-6674

Body Style:
Rectangular
Overall Length:
Between 1.910 inches and 2.262 inches
Overall Height:
0.500 inches
Overall Width:
1.344 inches
Frequency Rating:
18.0 gigahertz 2nd frequency voltage standing wave ratio and 21.0 gigahertz 2nd frequency voltage standing wave ratio
Switch Type:
Nontransfer
Operating Tempurature Range:
-15.0/+70.0 degrees celsius
Voltage Standing Wave Ratio:
1.50 2nd
Insertion Loss In Decibels:
0.50 2nd
Coaxial Connector Series Designation:
Sma
Connector End Design:
Female
Minimum Crosstalk Rating In Decibels:
60.0 single
Actuator Operating Method:
Solid state
Actuator Current Type And Rating In Amps:
0.18 dc
Actuator Voltage In Volts:
12.0
Switch Operation Sequence:
Breaks before makes
Switching Time:
50.0 milliseconds
Switch Return Mechanism Type:
Latching
Pole Quantity:
1
Throw Quantity:
2
Coupling Position Quantity:
3



### **Special Features:**

Two alternate mounting holes diameter 0.120 in. Each center to center 0.440 in.

### Material:

Copper alloy contact (s)

### Precious Material:

Gold

# Surface Treatment:

Nickel body outside surfaces

## Terminal Type And Quantity:

2 tab, solder lug and 3 receptacle, coaxial

Shelf Life:

N/a

### Unit Of Measure:

---

### Demilitarization:

Yes - demil/mli

### Fiig:

A158a0