## NSN 5985-01-201-3917



Fixed Attenuator - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5985-01-201-3917
Application Design:
Transmission line
Body Material:
Aluminum alloy
Body Style:
Round, terminal/terminals on one surface
Body Surface Treatment:
Any acceptable
Overall Height:
Between 0.740 inches and 0.760 inches
Overall Diameter:
Between 0.350 inches and 0.370 inches
Center To Center Distance Between Terminals:
0.100 inches
Operating Tempurature Range:
-55.0/+71.0 degrees celsius
End Application:
Radar set, an/sps-52c
Voltage Standing Wave Ratio:
1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Power Rating:
100.0 milliwatts peak
Rf Signal Attenuation In Decibels:
6.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+1.0 gigahertz
Attenuation Accuracy In Decibels:
-0.10/+0.10
Mounting Method:

Plug-in

**Terminal Type And Quantity:** 

3 pin

Frequency Range:

Between 0.000 hertz and 1.000 gigahertz

**Fsc Application Data:** 

Antennas, waveguides, and related equipment

Shelf Life:

N/a

## NSN 5985-01-201-3917

Fixed Attenuator - Page 2 of 2



		eas	

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000