NSN 5985-01-203-1202

Fixed Attenuator - Page 1 of 2

Application Design:



View Online at https://aerobasegroup.com/nsn/5985-01-203-1202

Transmission line
Body Material:
Any acceptable
Body Style:
1b round, terminal/terminals in opposite surface
Terminal Material:
Any acceptable
Terminal Surface Treatment:
Any acceptable
Body Surface Treatment:
Any acceptable
Overall Length:
1.300 inches
Overall Diameter:
Between 0.300 inches and 0.420 inches
Operating Tempurature Range:
+0.0/+65.0 degrees celsius
End Application:
Radar set an/sps-6 (v) 1
Voltage Standing Wave Ratio:
1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts peak
Rf Signal Attenuation In Decibels:
37.3
Voltage Standing Wave Ratio Frequency Range:
+5.4/+5.9 gigahertz
Connection Type Per Function:
Female input and male output
Unpackaged Unit Weight:
0.100 pounds
Mounting Method:
Connector

Terminal Type And Quantity:

2 connector

NSN 5985-01-203-1202

Fixed Attenuator - Page 2 of 2



Between 5.400 gigahertz and 5.900 gigahertz

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000