NSN 5985-01-207-0943

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-207-0943

Application Design:
Transmission line
Body Material:
Steel, corrosion resisting
Body Style:
Err-090
Body Surface Treatment:
Passivated
Overall Length:
0.860 inches
Overall Diameter:
0.310 inches
Operating Tempurature Range:
-54.0/+125.0 degrees celsius
End Application:
Nsn: 5821-01-455-1799, receiving set, radio
Voltage Standing Wave Ratio:
1.15 and 1.25 and 1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average and 100.0 watts peak
Rf Signal Attenuation In Decibels:
10.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
5 5
Criticality Code Justification:
Criticality Code Justification: Feat

Special Features:

Weapon system essential

NSN 5985-01-207-0943

Fixed Attenuator - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000