

View Online at <https://aerobasegroup.com/nsn/5985-01-207-0952>

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

2.260 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches

Overall Height:

3.120 inches

Overall Width:

1.500 inches

End Application:

6625-01-193-2198 modulator-noise generator type md-1173/g

Voltage Standing Wave Ratio:

1.40

Coaxial Connector Series Designation:

Sma

Power Rating:

1.0 watts average

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

1.2

Overall Attenuation Range In Decibels:

+0.0/+10.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

8 threaded hole

Frequency Range:

Between 0.000 hertz and 500.000 megahertz

Overall Attenuation Accuracy In Decibels:

-0.25/+0.25

Mounting Thread Quantity:

40 per inch

Adjustment Device Type And Quantity:

1 slotted screw

Mounting Facility Pattern:

Four position rectangular

Mounting Facility Screw Thread Diameter:

0.112 inches

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0