NSN 5985-01-207-6549

Fixed Attenuator - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5985-01-207-6549

Application Decima
Application Design: Transmission line
Body Material:
Aluminum
Body Style:
Err-090
Body Surface Treatment:
Any acceptable
Overall Length:
0.860 inches
Overall Diameter:
0.312 inches
Operating Tempurature Range:
-54.0/+95.0 degrees celsius
End Application:
An-alq184equi
Voltage Standing Wave Ratio:
1.15 and 1.20 and 1.25 and 1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Rf Signal Attenuation In Decibels:
15.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Temperature Sensitivity Attenuation In Decibels:
0.0001
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Shelf Life:

NSN 5985-01-207-6549

Fixed Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000