NSN 5985-01-208-0919

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-208-0919 **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** 1b round, terminal/terminals in opposite surface **Body Surface Treatment:** Passivated **Overall Length:** 1.200 inches **Overall Diameter:** 0.360 inches **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius **End Application:** 5895-01-193-2197 rf down converter type cv-3904/g **Voltage Standing Wave Ratio:** 1.15 and 1.20 and 1.25 and 1.35 **Input Impedance Rating In Ohms:** 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Wpm **Power Rating:** 2.0 watts average and 500.0 watts peak **Rf Signal Attenuation In Decibels:** 20.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0 to 4.0 gigahertz and +4.0 to 8.0 gigahertz and +8.0 to 12.4 gigahertz and +12.4 to 18.0 gigahertz **Attenuation Accuracy In Decibels:** -0.70 to 0.70 **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Shelf Life: N/a

Unit Of Measure:

NSN 5985-01-208-0919

Fixed Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A20000