## NSN 5985-01-208-3598

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-208-3598 **Application Design:** Transmission line **Body Material:** Steel, corrosion resisting **Body Style:** 1b round, terminal/terminals in opposite surface **Body Surface Treatment:** Passivated **Overall Length:** 2.490 inches **Overall Diameter:** 0.840 inches **End Application:** Radar set an/sps-4 (v7) **Voltage Standing Wave Ratio:** 1.15 and 1.20 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Ν **Power Rating:** 2.0 watts average and 500.0 watts peak **Rf Signal Attenuation In Decibels:** 3.0 **Voltage Standing Wave Ratio Frequency Range:** +0.5 to 1.0 gigahertz and +0.0 to 0.5 gigahertz **Attenuation Accuracy In Decibels:** -0.50 to 0.50 **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 1.000 gigahertz Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

## NSN 5985-01-208-3598

Fixed Attenuator - Page 2 of 2



Fiig:

A20000