

View Online at <https://aerobasegroup.com/nsn/5985-01-208-6398>

Body Style:

Rectangular

Overall Length:

1.970 inches

Overall Height:

0.500 inches

Overall Width:

1.500 inches

Frequency Rating:

0.0 gigahertz single frequency operating and 18.0 gigahertz single frequency operating

Unthreaded Mounting Hole Diameter:

0.120 inches

Switch Type:

Nontransfer

Longest Horizontal Distance Between Mounting Centers:

1.312 inches single mounting facility pattern

Operating Temperature Range:

-54.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

1.50 3rd

Insertion Loss In Decibels:

0.50 3rd

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Rf Power Handling Capability:

200.0 watts average single

Minimum Crosstalk Rating In Decibels:

70.0 2nd

Actuator Current Type And Rating In Amps:

0.17 dc

Actuator Voltage In Volts:

Between 24.0 and 30.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

20.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

1 base and 2 unthreaded hole

Mounting Facility Pattern:

Two position in-line single mounting facility pattern

Special Features:

Actuator operating method: solenoid

Material:

Aluminum alloy body

Surface Treatment:

Nickel body all surfaces and paint body all surfaces

Terminal Type And Quantity:

2 turret and 3 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0