NSN 5985-01-209-4643

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-209-4643 **Application Design:** Waveguide **Body Material:** Steel **Body Style:** Rectangular, terminal/terminals on one surface **Terminal Material:** Steel **Terminal Surface Treatment:** Gold plated **Body Surface Treatment:** Gold plated **Overall Length:** Between 0.490 inches and 0.530 inches **Overall Height:** 0.697 inches **Overall Width:** 0.150 inches **Body Height:** Between 0.365 inches and 0.405 inches **Operating Tempurature Range:** -54.0 to 95.0 degrees celsius **End Application:** Missile control, remote; acft **Voltage Standing Wave Ratio:** 2.10 **Rf Signal Attenuation In Decibels: Center To Center Distance Between First And Second Terminals:** 0.100 inches **Center To Center Distance Between Second And Third Terminals:** 0.150 inches **Center To Center Distance Between Third And Fourth Terminals:** 0.100 inches **Terminal Type And Quantity:** 8 wire lead Frequency Range: Between 10.000 megahertz and 50.000 megahertz

Fsc Application Data: Waveguide assembly Shelf Life:

N/a

NSN 5985-01-209-4643

Fixed Attenuator - Page 2 of 2



		eas	

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000