

View Online at <https://aerobasegroup.com/nsn/5985-01-210-2633>

Application Design:

Transmission line

Body Style:

Rectangular, terminals on one surface

Overall Length:

2.400 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 1.557 inches and 1.567 inches

Overall Height:

1.100 inches

Overall Width:

1.643 inches

Shaft Diameter:

0.255 inches

Bushing Length:

0.139 inches

Shaft Length:

0.062 inches

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.2

Overall Attenuation Range In Decibels:

+0.0 to 20.0

Attenuation Accuracy Reference Frequency:

60.0 hertz

Attenuation Variation Method:

Stepped

Step Position Quantity:

2

Attenuation Per Step In Decibels:

2.0

Mounting Facility Type And Quantity:

2 threaded hole

Frequency Range:

Between 50.000 megahertz and 70.000 megahertz

Overall Attenuation Accuracy In Decibels:

-0.100 to 0.100

Mounting Thread Quantity:

40 per inch

Adjustment Device Type And Quantity:

1 shaft and 1 slotted screw

Mounting Facility Pattern:

Two position diagonal

Shaft Type:

Round, slotted

Mounting Facility Screw Thread Diameter:

0.112 inches

Impedance Rating In Ohms:

50.0 input

Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A223a0