NSN 5985-01-211-5221

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-211-5221

Application Design:
Transmission line
Body Material:
Steel, corrosion resisting
Body Style:
1b round, terminal/terminals in opposite surface
Overall Length:
0.860 inches
Overall Diameter:
0.280 inches
Operating Tempurature Range:
-40.0 to 75.0 degrees celsius
End Application:
Receiving set, countermeasures an/alq-142
Voltage Standing Wave Ratio:
1.15 and 1.20 and 1.25 and 1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Rf Signal Attenuation In Decibels:
3.0
Voltage Standing Wave Ratio Frequency Range:
+0.0 to 4.0 gigahertz and +4.0 to 8.0 gigahertz and +8.0 to 12.4 gigahertz and +12.4 to 18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50 to 0.50
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Precious Material And Location:
Connector body surface option gold
Precious Material:
Gold
Shelf Life:

N/a

NSN 5985-01-211-5221

Fixed Attenuator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000