

View Online at <https://aerobasegroup.com/nsn/5985-01-211-5964>

Application Design:

Transmission line

Body Material:

Steel, corrosion resisting

Body Style:

Rectangular, terminal/terminals on opposite surfaces

Body Surface Treatment:

Passivated

Overall Length:

1.080 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.687 inches

Overall Height:

0.687 inches

Overall Width:

0.687 inches

Mounting Hole/stud Quantity:

4

Unthreaded Mounting Hole Diameter:

Between 0.120 inches and 0.128 inches

Operating Temperature Range:

-45.6 to 71.0 degrees celsius

End Application:

1430-01-087-6330 attenuator, fix

Voltage Standing Wave Ratio:

1.05 and 1.15

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Sma

Rf Signal Attenuation In Decibels:

14.5

Voltage Standing Wave Ratio Frequency Range:

+1.6 to 6.0 gigahertz

Attenuation Accuracy In Decibels:

-5.00 to 5.00

Temperature Sensitivity Attenuation In Decibels:

0.0001

Connection Type Per Function:

Female input and male output

Mounting Method:

Connector and flange w/mounting hole

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 1.600 gigahertz and 6.000 gigahertz

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000