NSN 5985-01-212-5631

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-212-5631

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Passivated
Overall Length:
Between 2.510 inches and 2.540 inches
Overall Diameter:
Between 0.780 inches and 0.810 inches
Operating Tempurature Range:
-20.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.40
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
1.0 watts average
1.0 watts average Rf Signal Attenuation In Decibels:
<u>-</u>
Rf Signal Attenuation In Decibels:
Rf Signal Attenuation In Decibels: 20.0
Rf Signal Attenuation In Decibels: 20.0 Voltage Standing Wave Ratio Frequency Range:
Rf Signal Attenuation In Decibels: 20.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+2.0 gigahertz
Rf Signal Attenuation In Decibels: 20.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+2.0 gigahertz Attenuation Accuracy Reference Frequency:
Rf Signal Attenuation In Decibels: 20.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+2.0 gigahertz Attenuation Accuracy Reference Frequency: 2.0 gigahertz
Rf Signal Attenuation In Decibels: 20.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+2.0 gigahertz Attenuation Accuracy Reference Frequency: 2.0 gigahertz Attenuation Accuracy In Decibels:
Rf Signal Attenuation In Decibels: 20.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+2.0 gigahertz Attenuation Accuracy Reference Frequency: 2.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00
Rf Signal Attenuation In Decibels: 20.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+2.0 gigahertz Attenuation Accuracy Reference Frequency: 2.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Mounting Method:
Rf Signal Attenuation In Decibels: 20.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+2.0 gigahertz Attenuation Accuracy Reference Frequency: 2.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Mounting Method: Connector
Rf Signal Attenuation In Decibels: 20.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+2.0 gigahertz Attenuation Accuracy Reference Frequency: 2.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Mounting Method: Connector Terminal Type And Quantity:
Rf Signal Attenuation In Decibels: 20.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+2.0 gigahertz Attenuation Accuracy Reference Frequency: 2.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Mounting Method: Connector Terminal Type And Quantity: 2 connector
Rf Signal Attenuation In Decibels: 20.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+2.0 gigahertz Attenuation Accuracy Reference Frequency: 2.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:
Rf Signal Attenuation In Decibels: 20.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+2.0 gigahertz Attenuation Accuracy Reference Frequency: 2.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 2.000 gigahertz
Rf Signal Attenuation In Decibels: 20.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+2.0 gigahertz Attenuation Accuracy Reference Frequency: 2.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 2.000 gigahertz Fsc Application Data:

NSN 5985-01-212-5631

Fixed Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A20000