

View Online at <https://aerobasegroup.com/nsn/5985-01-213-8531>

**Body Style:**

Rectangular

**Frequency Rating:**

8.0 gigahertz 3rd frequency voltage standing wave ratio and 12.4 gigahertz 3rd frequency voltage standing wave ratio

**Unthreaded Mounting Hole Diameter:**

0.116 inches

**Switch Type:**

Nontransfer

**Voltage Standing Wave Ratio:**

1.50 4th

**Insertion Loss In Decibels:**

0.40 3rd

**Coaxial Connector Series Designation:**

Sma

**Connector End Design:**

Female

**Minimum Crosstalk Rating In Decibels:**

60.0 single

**Actuator Operating Method:**

Solid state

**Switch Return Mechanism Type:**

Fail-safe

**Pole Quantity:**

1

**Throw Quantity:**

2

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Mounting Facility Pattern:**

Two position in-line single mounting facility pattern

**Material:**

Copper alloy contact (s)

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Surface Treatment:**

Nickel body outside surfaces

**Terminal Type And Quantity:**

3 receptacle, coaxial

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A158a0