NSN 5985-01-214-0856

Fixed Attenuator - Page 1 of 2



View Online a	t https://aerobasegroup.com/nsn/5985-01-214-0856
Application [Design:
Transmission	line
Body Materia	al:
Steel, stainle	ss
Body Style:	
1b round, ter	minal/terminals in opposite surface
Body Surface	e Treatment:
Passivated	
Overall Leng	th:
0.860 inches	
Overall Diam	eter:
0.280 inches	
Operating Te	empurature Range:
-65.0 to 125.0	degrees celsius
Voltage Stan	ding Wave Ratio:
1.07	
Input Impeda	ince Rating In Ohms:
50.0	
Output Impe	dance Rating In Ohms:
50.0	
Coaxial Conr	nector Series Designation:
Sma	
Power Rating	g:
2.0 watts aver	rage
Rf Signal Att	enuation In Decibels:
8.0	
Voltage Stan	ding Wave Ratio Frequency Range:
+0.0 to 8.0 giç	gahertz
Attenuation A	Accuracy Reference Frequency:
8.0 gigahertz	
Attenuation A	Accuracy In Decibels:
-0.30 to 0.30	
Connection 7	Type Per Function:
Female input	and male output
Mounting Me	ethod:
Connector	

2 connector

Frequency Range:

Terminal Type And Quantity:

Between 0.000 hertz and 8.000 gigahertz

Fsc Application Data:

Antennas, waveguides, and related equipment

NSN 5985-01-214-0856

Fixed Attenuator - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000