

View Online at <https://aerobasegroup.com/nsn/5985-01-214-0861>

Application Design:

Transmission line

Body Material:

Steel

Body Style:

1b round, terminal/terminals in opposite surface

Terminal Material:

Beryllium copper

Terminal Surface Treatment:

Gold plated

Body Surface Treatment:

Passivated

Overall Length:

1.020 inches

Overall Diameter:

0.280 inches

Operating Temperature Range:

-65.0 to 125.0 degrees celsius

Voltage Standing Wave Ratio:

1.07

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Sma

Power Rating:

2.0 watts average

Rf Signal Attenuation In Decibels:

11.0

Voltage Standing Wave Ratio Frequency Range:

+0.0 to 12.0 gigahertz

Attenuation Accuracy Reference Frequency:

12.0 gigahertz

Attenuation Accuracy In Decibels:

-0.50 to 0.50

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 12.000 gigahertz

Precious Material And Location:

Center conductor surfaces gold

Precious Material:

Gold

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000