

View Online at <https://aerobasegroup.com/nsn/5985-01-215-0814>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b first flange all connection facilities

**Thread Direction:**

Right-hand first flange all connection facilities

**Bend Angle In Deg:**

90.0 single bend e-plane

**Tubing Wall Construction Style:**

Seamless all tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

1.003 inches and 1.006 inches second flange

**Flange Inside Height:**

0.503 inches and 0.506 inches second flange

**Flange Outside Width:**

1.610 inches and 1.640 inches second flange

**Flange Outside Height:**

1.610 inches and 1.640 inches second flange

**Flange Inside Diameter:**

1.406 inches and 1.437 inches first flange

**Flange Depth:**

0.423 inches and 0.453 inches second flange

**Flange Connecting Hole Diameter:**

0.169 inches and 0.172 inches second flange all connection facilities

**Voltage Standing Wave Ratio:**

1.05

**Waveguide Outside Width:**

Between 0.996 inches and 1.004 inches

**Thread Size:**

0.164 inches first flange all connection facilities

**Waveguide Inside Width:**

Between 0.896 inches and 0.904 inches

**Waveguide Inside Height:**

Between 0.396 inches and 0.404 inches

**Waveguide Outside Height:**

Between 0.496 inches and 0.504 inches

**Waveguide Longer Offset Distance:**

2.000 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole second flange all connection facilities

**Flange Style:**

Cover type second flange

**Waveguide Offset Distance:**

2.000 inches

**Flexibility:**

Rigid all tubing segment

**Material:**

Aluminum alloy all tubing segment and flange

**Surface Treatment:**

Enamel all tubing segment and flange outside surfaces

**Style Designator:**

Bend type

**Thread Series Designator:**

Unc first flange all connection facilities

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0