NSN 5985-01-215-0814

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-215-0814

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Bend Angle In Deg:

90.0 single bend e-plane

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches and 1.006 inches second flange

Flange Inside Height:

0.503 inches and 0.506 inches second flange

Flange Outside Width:

1.610 inches and 1.640 inches second flange

Flange Outside Height:

1.610 inches and 1.640 inches second flange

Flange Inside Diameter:

1.406 inches and 1.437 inches first flange

Flange Depth:

0.423 inches and 0.453 inches second flange

Flange Connecting Hole Diameter:

0.169 inches and 0.172 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.05

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Thread Size:

0.164 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Waveguide Longer Offset Distance:

2.000 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

NSN 5985-01-215-0814

Waveguide Assembly - Page 2 of 2



Flange Style: Cover type second flange Waveguide Offset Distance: 2.000 inches Flexibility: Rigid all tubing segment Material: Aluminum alloy all tubing segment and flange Surface Treatment: Enamel all tubing segment and flange outside surfaces Style Designator: Bend type **Thread Series Designator:** Unc first flange all connection facilities **Fsc Application Data:** Antennas, waveguides, and related equipment Shelf Life: N/a Unit Of Measure: --Demilitarization: Yes - demil/mli Fiig: A073a0