

View Online at <https://aerobasegroup.com/nsn/5985-01-215-0840>

**Application Design:**

Transmission line

**Body Material:**

Steel, stainless

**Body Style:**

1b round, terminal/terminals in opposite surface

**Body Surface Treatment:**

Passivated

**Overall Length:**

0.860 inches

**Overall Diameter:**

0.280 inches

**Operating Temperature Range:**

-65.0 to 125.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.07

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

2.0 watts average

**Rf Signal Attenuation In Decibels:**

6.5

**Voltage Standing Wave Ratio Frequency Range:**

+0.0 to 8.0 gigahertz

**Attenuation Accuracy Reference Frequency:**

8.0 gigahertz

**Attenuation Accuracy In Decibels:**

-0.30 to 0.30

**Connection Type Per Function:**

Female input and male output

**Mounting Method:**

Connector

**Terminal Type And Quantity:**

2 connector

**Frequency Range:**

Between 0.000 hertz and 8.000 gigahertz

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A20000