## NSN 5985-01-215-3443

Fixed Attenuator - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5985-01-215-3443

1.0.1. C
Application Design:
Transmission line
Body Material:
Steel, corrosion resisting
Body Style:
Err-090
Body Surface Treatment:
Gold plated or passivated
Overall Length:
Between 0.840 inches and 0.880 inches
Overall Diameter:
0.300 inches
Operating Tempurature Range:
-40.0/+80.0 degrees celsius
End Application:
Countermeasures radar an/alq142
Voltage Standing Wave Ratio:
1.15 and 1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Rf Signal Attenuation In Decibels:
3.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Unpackaged Unit Weight:
0.200 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Shelf Life:
***

## NSN 5985-01-215-3443

Fixed Attenuator - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000