NSN 5985-01-215-4314

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-215-4314

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.300 inches
Overall Height:
1.503 inches
Overall Width:
1.100 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.438 inches
Unthreaded Mounting Hole Diameter:
0.144 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
1.5
Overall Attenuation Range In Decibels:
+0.0 to 25.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
2 unthreaded hole
Frequency Range:
Between 175.000 megahertz and 225.000 megahertz
Overall Attenuation Accuracy In Decibels:
-0.50 to 0.50
Adjustment Device Type And Quantity:
1 shaft
Shaft Type:
Round, slotted
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:

2 connector, coaxial, female

NSN 5985-01-215-4314

Variable Attenuator - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0