# NSN 5985-01-215-4719

Fixed Attenuator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5985-01-215-4719



# **Application Design:**

Transmission line

#### **Body Material:**

Steel, stainless

# Body Style:

1b round, terminal/terminals in opposite surface

## **Body Surface Treatment:**

Passivated

#### **Overall Length:**

1.240 inches

#### **Overall Diameter:**

Between 0.350 inches and 0.385 inches

#### **Operating Tempurature Range:**

-65.0 to 105.0 degrees celsius

#### Voltage Standing Wave Ratio:

## 1.15 and 1.30 and 1.35

## Input Impedance Rating In Ohms:

50.0

#### **Output Impedance Rating In Ohms:**

50.0

## **Coaxial Connector Series Designation:**

Sma

#### **Power Rating:**

2.0 watts average

## **Rf Signal Attenuation In Decibels:**

12.0

## Voltage Standing Wave Ratio Frequency Range:

+0.0 to 4.0 gigahertz and +4.0 to 12.4 gigahertz and +12.4 to 18.0 gigahertz

## Attenuation Accuracy In Decibels:

-0.75 to 0.75

## Mounting Method:

Connector

## **Terminal Type And Quantity:**

2 connector

## **Frequency Range:**

Between 0.000 hertz and 18.000 gigahertz

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5985-01-215-4719

Fixed Attenuator - Page 2 of 2

**Fiig:** A20000

