NSN 5985-01-216-2314

View Online at https://aerobasegroup.com/nsn/5985-01-216-2314

Fixed Attenuator - Page 1 of 2 **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** 1b round, terminal/terminals in opposite surface **Body Surface Treatment:** Passivated **Overall Length:** 0.860 inches **Overall Diameter:** 0.280 inches **Operating Tempurature Range:** -65.0 to 125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.07 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Power Rating:** 2.0 watts average **Rf Signal Attenuation In Decibels:** 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 18.0 gigahertz **Attenuation Accuracy In Decibels:** -0.03 to 0.03 **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector **Frequency Range:** Between 0.000 hertz and 18.000 gigahertz Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** Yes - demil/mli

NSN 5985-01-216-2314

Fixed Attenuator - Page 2 of 2

Fiig: A20000

